

Concrete Mixer

Regulatory area: NA
DBM



MODEL

Length (in)
Wheelbase (in)
Ground clearance (in)
Width (in)
Cab width (in)
Wheel steering range (in)

DBM2500

207
108
18
91
36
164

DBM3500

215
108
19
92
36
165

PERFORMANCE

Unladen weight (lb)	15542	16314
Maximum cross gradient	15%	15%
Maximum gradient unladen	45%	45%
Concrete yield	5512	7716
Fifth wheel rotation	±90°	±90°
Engine	Deutz TCD3.6	Deutz TCD3.6
Displacement / Cylinders (gal)	0.95/4	0.95/4
Engine power (kW/HP)	74.4/100	74.4/100
Anti-pollution technology	Stage V	Stage V
Fuel tank capacity (gal)	53	53
AdBlue tank capacity (gal)	5	5
Transmission type	Hydrostatic	Hydrostatic
Axles	Drop portal	Drop portal
Brakes	4 dry disc	4 dry disc
Automatic parking brake	●	●
Number of gears	2	2
Maximum speed (mph)	25	25
Hydraulic pump	LS	LS
Delivery / Pressure (gal/min-psi)	27.20-3.046	27.20-3.046

CAB

Seat with pneumatic suspension	—	—
ROPS cab	STANDARD	STANDARD
Cab controls	Levers	Levers
Cab suspension	—	—
Sun-shade	—	—
Permanent four-wheel drive	●	●
All-wheel steering	●	●
Standard tyres	405/70-20"	18-19.5"
Rear tow hooks	●	●
Automatic battery disconnect switch	●	●
Rear Camera	●	●
Steering modes	3	3

— NOT AVAILABLE • ● STANDARD • ○ OPTIONAL

Your Merlo dealer



MERLO S.P.A.

Data, specifications and illustrations contained in this document are indicative and not binding. Merlo S.p.A. pursues a policy of continuous research and development; therefore, products may differ from those described or be subject to change without prior notice. The products shown may include optional equipment.