The technical specifications for the **Hiab XS 244 EP-5 HiPro** *truck-mounted knuckle-boom loader crane are summarized below. This configuration combines an EP boom type (optimized for short-to-medium outreach tasks with high payloads) with 5 hydraulic extensions and the advanced HiPro control system. [1, 2]*

Performance & Capacity

- **Capacity Class:** *203 kNm (20.7 tm)*
- **Automatic Duty Control (ADC) Capacity:** *218 kNm (22.3 tm)*
- **Max Hydraulic Outreach:** *15.1 meters*
- **Max Manual Outreach:** *17.3 meters*
- **Lifting Height (Hydraulic / Manual):** *17.7 meters / 19.9 meters [1]*

Dimensions & Weights

- **Standard Crane Weight:** *3,000 kg (without stabilizers)*
- **Folded Width:** *2,500 mm*
- **Folded Height:** *2,335 mm*
- **High Seat Weight Addition:** *70 kg [1, 2]*

Hydraulics & Mechanics

- **Working Pressure:** *33.0 MPa*
- **Recommended Oil Flow:** *90–120 l/min*
- **Slewing Range:** *190° to 410°*
- **Slewing Torque:** *28.3 kNm [1]*

Are you verifying these specs for a **load chart calculation**, *looking for information on its* **HiPro remote control settings**, *or looking to source* **replacement hydraulic parts**?